

Product Description

10825



Applene Masterbatch

Processing Aid Masterbatch Extrusion (Film) Grade

Product Description	APPLENE 10825 PA, a specially designed masterbatch using Fluoroelastomer. This masterbatch is used to enhance the processability of LLDPE and is characterized by excellent dispersion. The concentrate contains 25% Fluoro elastomer. It is designed for ease of handling when being dispersed in the final resin. It has no effect on transparency of the film.
Appearance	White, opaque granules.
Application Area	The major application area is in the field of thin Polyolefin Films.
Addition Level	The required effects are obtained with the addition level of 0.05% to 0.15%

	Properties	Test Method	Condition	Unit	Typical Value*
Physical	Specific Gravity	ASTM D792	23°C	----	1.04
	Melt Flow Index	ASTM D1238	190°C/2.16 kg	g/10min	< 1.0
	Fluoro Elastomer Content	-	-	%	25

* Typical values only. Variations within normal tolerances are possible for various colours. All values are measured atleast 48 hours storage at 23°C/ 50% relative humidity

Note:

All the information given by APPL for use of these materials is given in good faith and to the best of our knowledge. The data, information, suggestion contained herein are given purely as guide. APPL does not guarantee the exact replication of the data by users since plastic testing is affected by a number of extraneous factors.

ENG/F/01

APPL Industries Ltd.

www.applindustries.com

Unit-I Plot No. - 2, Sector - 7, Industrial Estate, IMT Manesar, Gurgaon, Haryana, India - 122050
Phone No +91-124-4368231 (Pilot No.) Fax No +91-124-4368234, E-Mail: applmsr@touchtelindia.net

Unit-II 680/2, Pune Nagar Road, Koregaon Bhima, Tal Shirur, Pune, Maharashtra, India - 412216
Telefax No +91-2137-253195/ 96, E-Mail: applindus@vsnl.net